TECHNICAL PARAMETERS OF WATER HEATERS Parameters for the water heater and storage tank CTC EcoNomic 300 Model(s): Conventional water heater: Heat pump water heater: No Solar water heater: No NA Storage tank: No Back-up immersion heater: General data Declared load profile XL Energy efficiency class 38 % **Energy efficiency** η_{WH} Annual electricity consumption AEC 4451 kWh °C Factory thermostat setting 55 Sound power level indoor 15 L_WA Daily electricity consumption \mathbf{Q}_{elec} 20,230 Fossil and/or biomass fuel heated water heater NA kWh Daily fuel consumption Q_{fuel} NO_x NA Emissions of nitrogen oxides (dioxide) mg/kWh Solar heated water heater m^2 Collector aperture area NA A_{sol} Zero-loss efficiency η_0 NA $W/(m^2 K)$ First-order coefficient NA a_1 Second-order coefficient NA $W/(m^2 K)$ a_2 NA Incidence angle modifier IAM Pump power consumption (solpump) NA W Standby power consumption (solstandby) NA W Heat pump heated water heater NA dB Sound power level outdoors L_{WA} Technical paremeter at declared load profile Storage water heater (3XS, XXS, XS) NA Volym Mixed vol 40° Storage water heater (S, M, XL, XXL, 3XL, 4XL) 375 L DHW Smart controller Weekly fuel consumption with smart NA kWh Q fuel, week, smart NA kWh Weekly electricity consumption with smart Q elec, week, smart NA

180426

Specific precautions and end of life information:

Weekly fuel consumption without smart

Technical parameters for storagetank

Standing loss

Storage volume

Weekly electricity consumption without smart

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. Disposing of the product as household waste is not

kWh

kWh

W

Q fuel, week

Q elec, week

NA

NA

NA

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se **Detailed Contact data:**

S

V, Cact