

**Warm climate and Medium temperature**

Model(s):	<b>CTC GS 6</b>		
Air-to-water heat pump:	<b>No</b>	Energy efficiency class:	-
Water-to-water heat pump:	<b>No</b>	Controller class:	<b>VII</b> -
Brine-to-water heat pump:	<b>Yes</b>	Controller contribution:	<b>3,5</b> %
Low-temperature heat pump:	<b>No</b>	Package efficiency:	<b>140</b> %
Equipped with a supplementary heater:	<b>Yes</b>	Package efficiency class:	-
Heat pump combination heater:	<b>Yes</b>		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>137</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>na</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>na</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>5,2</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>2,91</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>5,5</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>3,50</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>5,7</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>4,32</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,3</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>3,05</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,2</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,91</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>3</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,99</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,6</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,003</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items							
Capacity control	<b>Fixed</b>			For air-to-water heat pumps: Rated air flow rate, outdoors	-	<b>na</b>	m <sup>3</sup> /h
Sound power level, indoors/ outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	<b>0,9</b>	m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>2134</b>	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	<b>XL / A</b>			Water heating energy efficiency	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170706		

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>designh</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.



**Warm climate and Low temperature**

Model(s):	<b>CTC GS 6</b>		
Air-to-water heat pump:	<b>No</b>	Energy efficiency class:	-
Water-to-water heat pump:	<b>No</b>	Controller class:	<b>VII</b> -
Brine-to-water heat pump:	<b>Yes</b>	Controller contribution:	<b>3,5</b> %
Low-temperature heat pump:	<b>No</b>	Package efficiency:	<b>181</b> %
Equipped with a supplementary heater:	<b>Yes</b>	Package efficiency class:	-
Heat pump combination heater:	<b>Yes</b>		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>7</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>178</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = - 7 °C	<i>P<sub>dh</sub></i>	<b>na</b>	kW	T <sub>j</sub> = - 7 °C	<i>COP<sub>d</sub></i>	<b>na</b>	-
T <sub>j</sub> = + 2 °C	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,56</b>	-
T <sub>j</sub> = + 7 °C	<i>P<sub>dh</sub></i>	<b>6,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>4,82</b>	-
T <sub>j</sub> = + 12 °C	<i>P<sub>dh</sub></i>	<b>6,2</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>5,17</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>4,67</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>4,56</b>	-
For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>3</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,6</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,005</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items	Capacity control: <b>Fixed</b>						
Sound power level, indoors/ outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>1892</b>	kWh	-	<b>1,2</b>	<b>m<sup>3</sup>/h</b>	

For heat pump combination heater:

<b>Declared load profile/ Energy efficiency class</b>	<b>XL / A</b>			<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170706		

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>designh</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.



**Average climate and Medium temperature**

Model(s):	CTC GS 6		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	143 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>140</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>5,3</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,18</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>5,6</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>3,80</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>5,7</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>4,19</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>4,62</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,4</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>3,30</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,2</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,91</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-6</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,99</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>1,1</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,003</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Fixed</b>			-			
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	dB	-			
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3583</b>	kWh	-			

For heat pump combination heater:

<b>Declared load profile/ Energy efficiency class</b>	<b>XL / A</b>			<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170706		

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>design,h</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.



**Average climate and Low temperature**

Model(s):	<b>CTC GS 6</b>		
Air-to-water heat pump:	<b>No</b>	Energy efficiency class:	<b>A++</b> -
Water-to-water heat pump:	<b>No</b>	Controller class:	<b>VII</b> -
Brine-to-water heat pump:	<b>Yes</b>	Controller contribution:	<b>3,5</b> %
Low-temperature heat pump:	<b>No</b>	Package efficiency:	<b>184</b> %
Equipped with a supplementary heater:	<b>Yes</b>	Package efficiency class:	<b>A+++</b> -
Heat pump combination heater:	<b>Yes</b>		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>7</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>181</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = - 7 °C	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = - 7 °C	<i>COP<sub>d</sub></i>	<b>4,67</b>	-
T <sub>j</sub> = + 2 °C	<i>P<sub>dh</sub></i>	<b>6,1</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,89</b>	-
T <sub>j</sub> = + 7 °C	<i>P<sub>dh</sub></i>	<b>6,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>5,08</b>	-
T <sub>j</sub> = + 12 °C	<i>P<sub>dh</sub></i>	<b>6,2</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>5,37</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>4,67</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>4,56</b>	-
For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-7</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,9</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,005</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Fixed</b>			-	<b>na</b>	<i>m<sup>3</sup>/h</i>	
Sound power level, indoors/ outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	<i>dB</i>	-	<b>1,2</b>	<i>m<sup>3</sup>/h</i>	
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3021</b>	<i>kWh</i>				

For heat pump combination heater:

<b>Declared load profile/ Energy efficiency class</b>	<b>XL / A</b>			<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170706		

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>design,h</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.



**Cold climate and Medium temperature**

Model(s):	<b>CTC GS 6</b>		
Air-to-water heat pump:	<b>No</b>	Energy efficiency class:	-
Water-to-water heat pump:	<b>No</b>	Controller class:	<b>VII</b> -
Brine-to-water heat pump:	<b>Yes</b>	Controller contribution:	<b>3,5</b> %
Low-temperature heat pump:	<b>No</b>	Package efficiency:	<b>147</b> %
Equipped with a supplementary heater:	<b>Yes</b>	Package efficiency class:	-
Heat pump combination heater:	<b>Yes</b>		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>143</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>5,5</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,65</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>5,7</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,12</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>4,47</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>5,9</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>4,75</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,3</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>3,18</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,2</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,91</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-18</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,99</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,9</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,003</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Fixed</b>			-	<b>na</b>	<i>m<sup>3</sup>/h</i>	
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	<i>dB</i>	-	<b>0,9</b>	<i>m<sup>3</sup>/h</i>	
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3931</b>	<i>kWh</i>				

For heat pump combination heater:

<b>Declared load profile/ Energy efficiency class</b>	<b>XL / A</b>			<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170706		

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>designh</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.



**Cold climate and Low temperature**

Model(s):	<b>CTC GS 6</b>		
Air-to-water heat pump:	<b>No</b>	Energy efficiency class:	-
Water-to-water heat pump:	<b>No</b>	Controller class:	<b>VII</b> -
Brine-to-water heat pump:	<b>Yes</b>	Controller contribution:	<b>3,5</b> %
Low-temperature heat pump:	<b>No</b>	Package efficiency:	<b>188</b> %
Equipped with a supplementary heater:	<b>Yes</b>	Package efficiency class:	-
Heat pump combination heater:	<b>Yes</b>		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>7</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>184</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = - 7 °C	<i>P<sub>dh</sub></i>	<b>6,1</b>	kW	T <sub>j</sub> = - 7 °C	<i>COP<sub>d</sub></i>	<b>4,89</b>	-
T <sub>j</sub> = + 2 °C	<i>P<sub>dh</sub></i>	<b>6,1</b>	kW	T <sub>j</sub> = + 2 °C	<i>COP<sub>d</sub></i>	<b>5,08</b>	-
T <sub>j</sub> = + 7 °C	<i>P<sub>dh</sub></i>	<b>6,2</b>	kW	T <sub>j</sub> = + 7 °C	<i>COP<sub>d</sub></i>	<b>5,26</b>	-
T <sub>j</sub> = + 12 °C	<i>P<sub>dh</sub></i>	<b>6,2</b>	kW	T <sub>j</sub> = + 12 °C	<i>COP<sub>d</sub></i>	<b>5,26</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>4,67</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>6,0</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>4,56</b>	-
For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = - 15 °C (if TOL < - 20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-19</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>na</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cy</sub></i>	<b>na</b>	-
Degradation co-efficient (**)	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>65</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,018</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,7</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,005</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,018</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Fixed</b>			-			
Sound power level, indoors/ outdoors	<i>L<sub>WA</sub></i>	<b>41/na</b>	dB	-			
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3402</b>	kWh	-			

For heat pump combination heater:

<b>Declared load profile/ Energy efficiency class</b>	<b>XL / A</b>			<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>100</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7,659</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>na</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1685</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>na</b>	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se		170706	

(\*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P<sub>rated</sub>* is equal to the design load for heating *P<sub>designh</sub>*, and the rated heat output of a supplementary heater *P<sub>sup</sub>* is equal to the supplementary capacity for heating *sup(T<sub>j</sub>)*. (\*\*) If *C<sub>dh</sub>* is not determined by measurement then the default degradation coefficient is *C<sub>dh</sub>* = 0,9.