

Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	139 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	135	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	7,6	kW	T _j = +2 °C	<i>COP_d</i>	3,13	-
T _j = +7 °C	<i>P_{dh}</i>	7,8	kW	T _j = +7 °C	<i>COP_d</i>	3,46	-
T _j = +12 °C	<i>P_{dh}</i>	8,0	kW	T _j = +12 °C	<i>COP_d</i>	4,12	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,22	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3083	kWh				
For heat pump combination heater:							
Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	181 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	177	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	8,2	kW	T _j = +2 °C	<i>COP_d</i>	4,58	-
T _j = + 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,81	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,09	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,66	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	2558	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	140 %
Equipped with a supplementary heater:	No	Package efficiency class:	A++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	9	kW	Seasonal space heating energy efficiency	η_s	136	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = - 7 °C	<i>Pdh</i>	7,7	kW	T j = - 7 °C	<i>COPd</i>	3,28	-
T j = + 2 °C	<i>Pdh</i>	7,9	kW	T j = +2 °C	<i>COPd</i>	3,62	-
T j = + 7 °C	<i>Pdh</i>	8,0	kW	T j = +7 °C	<i>COPd</i>	4	-
T j = + 12 °C	<i>Pdh</i>	8,1	kW	T j = +12 °C	<i>COPd</i>	4,38	-
T j = bivalent temperature	<i>Pdh</i>	7,7	kW	T j = bivalent temperature	<i>COPd</i>	3,13	-
T j = operation limit temperature	<i>Pdh</i>	na	kW	T j = operation limit temperature	<i>COPd</i>	3,28	-
For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>Pdh</i>	na	kW	For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>COPd</i>	na	-
Bivalent temperature	<i>T biv</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P cych</i>	na	kW	Cycling interval efficiency	<i>COPcyc</i>	na	-
Degradation co-efficient (**)	<i>Cdh</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P OFF</i>	0,018	kW	Rated heat output (*)	<i>Psup</i>	1,1	kW
Thermostat-off mode	<i>P TO</i>	0,004	kW	Type of energy input Electric			
Standby mode	<i>P SB</i>	0,018	kW				
Crankcase heater mode	<i>P CK</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	<i>m3/h</i>	
Sound power level, indoors/ outdoors	<i>L WA</i>	46/na	<i>dB</i>	-	1,6	<i>m3/h</i>	
Annual energy consumption	<i>Q HE</i>	4995	<i>kWh</i>				
For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	na			η_{wh}	na	%	
Daily electricity consumption	<i>Qelec</i>	na	kWh	Daily fuel consumption	<i>Qfuel</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *Prated* is equal to the design load for heating *Pdesignh*, and the rated heat output of a supplementary heater *Psup* is equal to the supplementary capacity for heating *sup(Tj)*. (**) If *Cdh* is not determined by measurement then the default degradation coefficient is *Cdh* = 0,9.



Average climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	184 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	180	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,67	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	4,86	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	5,04	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,21	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4092	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{design,h}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	143 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	139	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	7,8	kW	T _j = -7 °C	<i>COP_d</i>	3,55	-
T _j = +2 °C	<i>P_{dh}</i>	8,0	kW	T _j = +2 °C	<i>COP_d</i>	3,92	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,27	-
T _j = +12 °C	<i>P_{dh}</i>	8,2	kW	T _j = +12 °C	<i>COP_d</i>	4,52	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,28	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5773	kWh				
For heat pump combination heater:							
Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoLogic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	187 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	183	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,3	kW	T _j = -7 °C	<i>COP_d</i>	4,88	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	5,04	-
T _j = +7 °C	<i>P_{dh}</i>	8,4	kW	T _j = +7 °C	<i>COP_d</i>	5,16	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,19	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-19	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	-	2,0	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4612	kWh				
For heat pump combination heater:							
Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	139 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	135	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = +2 °C	<i>COP_d</i>	3,13	-
T _j = + 7 °C	<i>P_{dh}</i>	7,8	kW	T _j = +7 °C	<i>COP_d</i>	3,46	-
T _j = + 12 °C	<i>P_{dh}</i>	8,0	kW	T _j = +12 °C	<i>COP_d</i>	4,12	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,22	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3083	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	181 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	177	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	8,2	kW	T _j = +2 °C	<i>COP_d</i>	4,58	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,81	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,09	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,66	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	2558	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	140 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	136	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,7	kW	T _j = - 7 °C	<i>COP_d</i>	3,28	-
T _j = + 2 °C	<i>P_{dh}</i>	7,9	kW	T _j = +2 °C	<i>COP_d</i>	3,62	-
T _j = + 7 °C	<i>P_{dh}</i>	8,0	kW	T _j = +7 °C	<i>COP_d</i>	4	-
T _j = + 12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,38	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	3,28	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4995	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Average climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	184 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A+++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	180	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,67	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	4,86	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	5,04	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,21	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4092	kWh				
For heat pump combination heater:							
Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	143 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	139	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	7,8	kW	T _j = -7 °C	<i>COP_d</i>	3,55	-
T _j = +2 °C	<i>P_{dh}</i>	8,0	kW	T _j = +2 °C	<i>COP_d</i>	3,92	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,27	-
T _j = +12 °C	<i>P_{dh}</i>	8,2	kW	T _j = +12 °C	<i>COP_d</i>	4,52	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,28	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5773	kWh				
For heat pump combination heater:							
Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith i350/ i350F		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	187 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low- temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	183	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = - 7 °C	<i>COP_d</i>	4,88	-
T _j = + 2 °C	<i>P_{dh}</i>	8,3	kW	T _j = + 2 °C	<i>COP_d</i>	5,04	-
T _j = + 7 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 7 °C	<i>COP_d</i>	5,16	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 12 °C	<i>COP_d</i>	5,19	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-19	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4612	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	103	%
Daily electricity consumption	<i>Q_{elec}</i>	7,420	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1632	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170710		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	128 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	124	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = +2 °C	<i>COP_d</i>	2,91	-
T _j = + 7 °C	<i>P_{dh}</i>	7,8	kW	T _j = +7 °C	<i>COP_d</i>	3,22	-
T _j = + 12 °C	<i>P_{dh}</i>	8,0	kW	T _j = +12 °C	<i>COP_d</i>	3,80	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,00	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,018	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3356	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	88,1	%
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{design,h}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	158 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	154	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	8,2	kW	T _j = +2 °C	<i>COP_d</i>	4,19	-
T _j = + 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,38	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	4,63	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,25	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,055	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	2910	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	88,1	%
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	129 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	125	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,7	kW	T _j = - 7 °C	<i>COP_d</i>	3,05	-
T _j = + 2 °C	<i>P_{dh}</i>	7,9	kW	T _j = +2 °C	<i>COP_d</i>	3,39	-
T _j = + 7 °C	<i>P_{dh}</i>	8,0	kW	T _j = +7 °C	<i>COP_d</i>	3,71	-
T _j = + 12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,03	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,11	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,5	kW
Thermostat-off mode	<i>P_{TO}</i>	0,018	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5670	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	88,1	%
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	163 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	10	kW	Seasonal space heating energy efficiency	η_s	159	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,27	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	4,44	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,59	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	4,73	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,31	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,5	kW
Thermostat-off mode	<i>P_{TO}</i>	0,055	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4816	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	88,1	%
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	131 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	127	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	7,8	kW	T _j = -7 °C	<i>COP_d</i>	3,31	-
T _j = +2 °C	<i>P_{dh}</i>	8,0	kW	T _j = +2 °C	<i>COP_d</i>	3,63	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	3,92	-
T _j = +12 °C	<i>P_{dh}</i>	8,2	kW	T _j = +12 °C	<i>COP_d</i>	4,14	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,05	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,018	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	6273	kWh				
For heat pump combination heater:							
Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	88,1	%
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 250		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	165 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	161	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = - 7 °C	<i>COP_d</i>	4,46	-
T _j = + 2 °C	<i>P_{dh}</i>	8,3	kW	T _j = + 2 °C	<i>COP_d</i>	4,59	-
T _j = + 7 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 7 °C	<i>COP_d</i>	4,69	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 12 °C	<i>COP_d</i>	4,71	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,3	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,96	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,055	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5383	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	L / A			Water heating energy efficiency	η_{wh}	Value	Unit
Daily electricity consumption	<i>Q_{elec}</i>	5,292	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1164	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	128 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	124	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	7,6	kW	T _j = +2 °C	<i>COP_d</i>	2,91	-
T _j = +7 °C	<i>P_{dh}</i>	7,8	kW	T _j = +7 °C	<i>COP_d</i>	3,22	-
T _j = +12 °C	<i>P_{dh}</i>	8,0	kW	T _j = +12 °C	<i>COP_d</i>	3,80	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,00	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,014	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3015	kWh				
For heat pump combination heater:							
Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{design,h}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	162 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	158	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	8,2	kW	T _j = +2 °C	<i>COP_d</i>	4,19	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,38	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	4,63	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,25	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,035	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	2439	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	130 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	126	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,7	kW	T _j = - 7 °C	<i>COP_d</i>	3,05	-
T _j = + 2 °C	<i>P_{dh}</i>	7,9	kW	T _j = +2 °C	<i>COP_d</i>	3,39	-
T _j = + 7 °C	<i>P_{dh}</i>	8,0	kW	T _j = +7 °C	<i>COP_d</i>	3,71	-
T _j = + 12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,03	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,11	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,5	kW
Thermostat-off mode	<i>P_{TO}</i>	0,014	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5248	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{design,h}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	165 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	161	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,27	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	4,43	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	4,58	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	4,73	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,27	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,035	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4542	kWh				

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	132 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	128	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	7,8	kW	T _j = -7 °C	<i>COP_d</i>	3,31	-
T _j = +2 °C	<i>P_{dh}</i>	8,0	kW	T _j = +2 °C	<i>COP_d</i>	3,64	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	3,93	-
T _j = +12 °C	<i>P_{dh}</i>	8,2	kW	T _j = +12 °C	<i>COP_d</i>	4,14	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,09	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	2,91	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-17	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,3	kW
Thermostat-off mode	<i>P_{TO}</i>	0,014	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5781	kWh				
For heat pump combination heater:							
Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC EcoZenith 550		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VII -
Brine-to-water heat pump:	Yes	Controller contribution:	3,5 %
Low-temperature heat pump:	No	Package efficiency:	167 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	163	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = - 7 °C	<i>COP_d</i>	4,46	-
T _j = + 2 °C	<i>P_{dh}</i>	8,3	kW	T _j = + 2 °C	<i>COP_d</i>	4,59	-
T _j = + 7 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 7 °C	<i>COP_d</i>	4,69	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 12 °C	<i>COP_d</i>	4,71	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,30	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,19	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,035	kW	Type of energy input Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-			
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	-			
Annual energy consumption	<i>Q_{HE}</i>	4374	kWh	-			

For heat pump combination heater:

Declared load profile/ Energy efficiency class	XL / A			Water heating energy efficiency	η_{wh}	102	%
Daily electricity consumption	<i>Q_{elec}</i>	7,449	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	1639	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170904		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	136 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	135	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = +2 °C	<i>COP_d</i>	3,13	-
T _j = + 7 °C	<i>P_{dh}</i>	7,8	kW	T _j = +7 °C	<i>COP_d</i>	3,46	-
T _j = + 12 °C	<i>P_{dh}</i>	8,0	kW	T _j = +12 °C	<i>COP_d</i>	4,12	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,22	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3083	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170410		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	178 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>Prated</i>	9	kW	Seasonal space heating energy efficiency	η_s	177	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T j			
T j = - 7 °C	<i>Pdh</i>	na	kW	T j = - 7 °C	<i>COPd</i>	na	-
T j = + 2 °C	<i>Pdh</i>	8,2	kW	T j = +2 °C	<i>COPd</i>	4,58	-
T j = + 7 °C	<i>Pdh</i>	8,3	kW	T j = +7 °C	<i>COPd</i>	4,81	-
T j = + 12 °C	<i>Pdh</i>	8,4	kW	T j = +12 °C	<i>COPd</i>	5,09	-
T j = bivalent temperature	<i>Pdh</i>	8,2	kW	T j = bivalent temperature	<i>COPd</i>	4,66	-
T j = operation limit temperature	<i>Pdh</i>	8,2	kW	T j = operation limit temperature	<i>COPd</i>	4,58	-
For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>Pdh</i>	na	kW	For air-to-water heat pumps: T j = - 15 °C (if TOL < - 20 °C)	<i>COPd</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>Cdh</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	m ³ /h	
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	-	2,0	m ³ /h	
Annual energy consumption	<i>Q_{HE}</i>	2558	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170410		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *Prated* is equal to the design load for heating *Pdesignh*, and the rated heat output of a supplementary heater *Psup* is equal to the supplementary capacity for heating *sup(Tj)*. (**) If *Cdh* is not determined by measurement then the default degradation coefficient is *Cdh* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	137 %
Equipped with a supplementary heater:	No	Package efficiency class:	A++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	136	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	7,7	kW	T _j = -7 °C	<i>COP_d</i>	3,28	-
T _j = +2 °C	<i>P_{dh}</i>	7,9	kW	T _j = +2 °C	<i>COP_d</i>	3,62	-
T _j = +7 °C	<i>P_{dh}</i>	8,0	kW	T _j = +7 °C	<i>COP_d</i>	4	-
T _j = +12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,38	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	na	kW	T _j = operation limit temperature	<i>COP_d</i>	3,28	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-6	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4995	kWh				
For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	na			Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Annual electricity consumption	<i>AEC</i>	na	kWh				
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se		170410	

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{design,h}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	181 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	180	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,67	-
T _j = +2 °C	<i>P_{dh}</i>	8,3	kW	T _j = +2 °C	<i>COP_d</i>	4,86	-
T _j = +7 °C	<i>P_{dh}</i>	8,3	kW	T _j = +7 °C	<i>COP_d</i>	5,04	-
T _j = +12 °C	<i>P_{dh}</i>	8,4	kW	T _j = +12 °C	<i>COP_d</i>	5,21	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	-	2,0	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4092	kWh				
For heat pump combination heater:				Water heating energy efficiency			
Declared load profile	na			η_{wh}	na	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se		170410	

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	140 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	139	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,8	kW	T _j = - 7 °C	<i>COP_d</i>	3,55	-
T _j = + 2 °C	<i>P_{dh}</i>	8,0	kW	T _j = +2 °C	<i>COP_d</i>	3,92	-
T _j = + 7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,27	-
T _j = + 12 °C	<i>P_{dh}</i>	8,2	kW	T _j = +12 °C	<i>COP_d</i>	4,52	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,7	kW	T _j = bivalent temperature	<i>COP_d</i>	3,28	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-18	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	1,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,6	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5773	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170410		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC Basicstyrning		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	184 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	183	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	8,3	kW	T _j = - 7 °C	<i>COP_d</i>	4,88	-
T _j = + 2 °C	<i>P_{dh}</i>	8,3	kW	T _j = + 2 °C	<i>COP_d</i>	5,04	-
T _j = + 7 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 7 °C	<i>COP_d</i>	5,16	-
T _j = + 12 °C	<i>P_{dh}</i>	8,4	kW	T _j = + 12 °C	<i>COP_d</i>	5,19	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,67	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-19	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,018	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input Electric			
Standby mode	<i>P_{SB}</i>	0,018	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-	na	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	-	2,0	2,0	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4612	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	170410		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Warm climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	110 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	109	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 2 °C	<i>COP_d</i>	3,13	-
T _j = + 7 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 7 °C	<i>COP_d</i>	3,03	-
T _j = + 12 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 12 °C	<i>COP_d</i>	2,92	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,6	kW	T _j = bivalent temperature	<i>COP_d</i>	3,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	1	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,5	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3756	kWh				

For heat pump combination heater:

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Declared load profile		na		Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Warm climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	162 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	161	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	na	kW	T _j = - 7 °C	<i>COP_d</i>	na	-
T _j = + 2 °C	<i>P_{dh}</i>	8,2	kW	T _j = +2 °C	<i>COP_d</i>	4,58	-
T _j = + 7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,44	-
T _j = + 12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,26	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,58	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	3	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	0,6	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,9	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	2796	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Average climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	A+ -
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	111 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	110	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,6	kW	T _j = - 7 °C	<i>COP_d</i>	3,13	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 2 °C	<i>COP_d</i>	3,01	-
T _j = + 7 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 7 °C	<i>COP_d</i>	2,94	-
T _j = + 12 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 12 °C	<i>COP_d</i>	2,87	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,6	kW	T _j = bivalent temperature	<i>COP_d</i>	3,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	1	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-			
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	-			
Annual energy consumption	<i>Q_{HE}</i>	6029	kWh	-			

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	A++ -
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	164 %
Equipped with a supplementary heater:	No	Package efficiency class:	A++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	163	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,2	kW	T _j = -7 °C	<i>COP_d</i>	4,58	-
T _j = +2 °C	<i>P_{dh}</i>	8,1	kW	T _j = +2 °C	<i>COP_d</i>	4,40	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,30	-
T _j = +12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,20	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,58	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-7	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	1,1	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,9	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	4467	kWh				

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se	161107		

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.



Cold climate and Medium temperature

Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	111 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	8	kW	Seasonal space heating energy efficiency	η_s	110	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = - 7 °C	<i>P_{dh}</i>	7,6	kW	T _j = - 7 °C	<i>COP_d</i>	3,02	-
T _j = + 2 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 2 °C	<i>COP_d</i>	2,94	-
T _j = + 7 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 7 °C	<i>COP_d</i>	2,90	-
T _j = + 12 °C	<i>P_{dh}</i>	7,6	kW	T _j = + 12 °C	<i>COP_d</i>	2,86	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,6	kW	T _j = bivalent temperature	<i>COP_d</i>	3,13	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,6	kW	T _j = operation limit temperature	<i>COP_d</i>	3,13	-
For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-19	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	1	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	0,7	kW
Thermostat-off mode	<i>P_{TO}</i>	0,004	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Fixed			-			
Sound power level, indoors/outdoors	<i>L_{WA}</i>	46/na	dB	-			
Annual energy consumption	<i>Q_{HE}</i>	6950	kWh	-			

For heat pump combination heater:

Declared load profile	na			Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.

Cold climate and Low temperature

Model(s):	CTC EcoPart 408 + CTC Basic		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	I -
Brine-to-water heat pump:	Yes	Controller contribution:	1 %
Low-temperature heat pump:	No	Package efficiency:	163 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	9	kW	Seasonal space heating energy efficiency	η_s	162	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	8,1	kW	T _j = -7 °C	<i>COP_d</i>	4,41	-
T _j = +2 °C	<i>P_{dh}</i>	8,1	kW	T _j = +2 °C	<i>COP_d</i>	4,30	-
T _j = +7 °C	<i>P_{dh}</i>	8,1	kW	T _j = +7 °C	<i>COP_d</i>	4,23	-
T _j = +12 °C	<i>P_{dh}</i>	8,1	kW	T _j = +12 °C	<i>COP_d</i>	4,17	-
T _j = bivalent temperature	<i>P_{dh}</i>	8,2	kW	T _j = bivalent temperature	<i>COP_d</i>	4,58	-
T _j = operation limit temperature	<i>P_{dh}</i>	8,2	kW	T _j = operation limit temperature	<i>COP_d</i>	4,58	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-20	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cy}</i>	na	-
Degradation co-efficient (**)	<i>C_{dh}</i>	0,99	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,007	kW	Rated heat output (*)	<i>P_{sup}</i>	0,5	kW
Thermostat-off mode	<i>P_{TO}</i>	0,013	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,007	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Fixed			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	46/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,9	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	5009	kWh				

For heat pump combination heater:

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Declared load profile		na		Water heating energy efficiency	η_{wh}	na	%
Daily electricity consumption	<i>Q_{elec}</i>	na	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	NA	kWh
Annual electricity consumption	<i>AEC</i>	na	kWh	Annual fuel consumption	<i>AFC</i>	NA	GJ
Contact details	Enertech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000			www.ctc.se			

(*) For heat pump space heaters and heat pump combination heaters, the rated heat output *P_{rated}* is equal to the design load for heating *P_{designh}*, and the rated heat output of a supplementary heater *P_{sup}* is equal to the supplementary capacity for heating *sup(T_j)*. (**) If *C_{dh}* is not determined by measurement then the default degradation coefficient is *C_{dh}* = 0,9.