

TECHNICAL PARAMETERS OF WATER HEATERS



Parameters for the water heater and storage tank

Model(s):	CTC Ackumulatortank 1. 300/20 2. 300		
Conventional water heater:	No		
Heat pump water heater:	No		
Solar water heater:	No		
Storage tank:	Yes	Back-up immersion heater:	No

General data

Daily electricity consumption	Q_{elec}	NA	kWh
Energy efficiency	wh	NA	%
Energy efficiency class	-	C	-
Annual electricity consumption	AEC	NA	kWh
Declared load profile	-	NA	-
Sound power level indoors	L_{WA}	15	dB

Fossil and/or biomass fuel heated water heater

Daily electricity consumption	Q_{fuel}	NA	kWh
Emissions of nitrogen oxides (dioxide)	NO_x	NA	mg/kWh

Solar heated water heater

Collector aperture area	A_{sol}	Na	m^2
Zero-loss efficiency	η_0	Na	-
First-order coefficient	a_1	Na	W/(m^2 K)
Second-order coefficient	a_2	Na	W/(m^2 K)
Incidence angle modifier	IAM	Na	-
Pump power consumption	(solpump)	Na	W
Standby power consumption	(solstandby)	Na	W

Heat pump heated water heater

Sound power level outdoors	L_{WA}	NA	dB
----------------------------	----------	----	----

Technical parameter at declared load profile

Storage water heater (3XS, XXS, XS)	Volym	NA	L
Storage water heater (S, M, XL, XXL, 3XL, 4XL)	Blandad vol 40° VV	NA	L

Smart controller

Weekly fuel consumption with smart	$Q_{fuel, week, smart}$	NA	kWh
Weekly electricity consumption with smart	$Q_{elec, week, smart}$	NA	kWh
Weekly fuel consumption without smart	$Q_{fuel, week}$	NA	kWh
Weekly electricity consumption without smart	$Q_{elec, week}$	NA	kWh

Technical parameters for storagetank

Storage volume	V	293	L
Standing loss	S	78,0	W

Detailed contact data:

Enertech AB, Box 309, 341 26 Ljungby www.ctc.se